

SUBARU/360



\$1,297.* UP TO **66 miles**
per gallon

*Suggested retail price P.O.E.



\$1,297.

Suggested retail price P.O.E.

UP
TO **66 miles**
per gallon

SUBARU/360

SPECIFICATIONS

DIMENSIONS & WEIGHTS

Overall Length	117.9 in.
Overall Width	51.2 in.
Overall Height	53.1 in.
Wheelbase	70.9 in.
Tread (Front)	44.9 in.
Tread (Rear)	42.1 in.
Ground Clearance	6.3 in.
Vehicle Weight	925.0 lb.
Seating Capacity	4 adults
Total Vehicle Weight	1,756.2 lb.

PERFORMANCE

Maximum Speed	69.3 mph
Cruising Speed	51.0 mph
Climbing Ability (sin. 0)	0.337
Turning Circle	26.2 ft.
Braking Distance	39.4 ft. at 31 mph

ENGINE

Model and Type	EK-32 Air-cooled, 2-stroke, 2 cyl. Engine
Bore x Stroke	2.42 in. x 2.36 in.
Piston Displacement	21.7 cu. in.
Compression Ratio	6.7 : 1
Maximum Output	25 hp/5,500 rpm
Maximum Torque	25.4 ft./4,500 rpm

ELECTRICAL EQUIPMENT

Battery	12V—26AH
Generator	12V—200W
Starter	12V—600W

CLUTCH

Type	Dry Single Plate
------	------------------

FUEL AND OIL TANK CAPACITIES

Fuel Tank	5.60 US gal.
Oil Tank	2.60 US qt.

TRANSMISSION

No. of Speeds	4-speed forward, 1-reverse
Transmission Type	Synchromeshed on 2nd, 3rd, and Top speed, selective sliding on reverse
Gear Ratios	1st: 3.130 2nd: 1.601 3rd: 1.000 Over Top: 0.806 Rev: 4.248
Final Reduction Gear	Helical Gear
Final Reduction Gear Ratio	3.667

STEERING SYSTEM

Type	Rack and Pinion
Gear Ratio	20.6 : 1

TIRES

Size	4.80—10—2
------	-----------

SUSPENSIONS

Front Axle	Trailing Arm Type Independent Suspension
Rear Axle	Swing Axle Type Independent Suspension
Front Spring	Torsion Bar and Coil Spring
Rear Spring	Torsion Bar

BRAKE SYSTEM

Front Brake	Hydraulic two Leading Type
Rear Brake	Hydraulic leading Trailing Type
Parking Brake	Mechanical on rear wheels

BODY

Type	Monocoque
------	-----------